



MICRO POWER
CENTRAL SUPPLY EMERGENCY LIGHT
 SERIES : CT12-5



BATTERY
ISO 9002



SPECIFICATIONS

- INPUT VOLTAGE : 220 V AC/50Hz +/-10%
- TYPE OF BATTERY : SEALED LEAD ACID
- LAMP USED : SEALED DICHROIC TUNGSTEN HALOGEN
- MODE OF OPERATION : NON MAINTAINED
- OPERATING TEMPERATURE : Ta 40 C
- CHARGER : CONSTANT VOLTAGE & CURRENT LIMIT
- CHARGER CURRENT : LIMITS CURRENT TO 100% OF FULL LOAD
CURRENT DOWN TO SHORT CIRCUIT CONDITION
- PROTECTION : AC.FUSE / DC.FUSE / LOW VOLTAGE CUT OFF TO
PREVENT BATTERY OVER DISCHARGE
- CONSTRUCTION : ELECTRO GALVANISED STEEL CASE EPOXY POWER COATED
- COMPLIANCE : IEC. 598-2-22

| MODEL | BATTERY SEALED LEAD ACID | LAMP HEAD | LAMP WATT | DURATION | WEIGHT |
|-------------|-----------------------------|---------------------|--------------|----------|--------|
| CT12-5CD(S) | 12V - 5Ah | DOWN LIGHT (SQUARE) | 20 | 2 HR. | 4 KG. |
| | | | 40 | 1 HR. | 4 KG. |
| | | | | | |