




MICRO POWER
CENTRAL SUPPLY EMERGENCY LIGHT
 SERIES : CTX12-120



BATTERY
ISO 9002



SPECIFICATIONS

- INPUT VOLTAGE : 220 V AC/50Hz +/-10%
- TYPE OF BATTERY : SEALED LEAD ACID
- MODE OF OPERATION : NON-MAINTAINED
- OPERATING TEMPERATURE : Ta 40 C
- CHARGER : TWO STEP CONSTANT VOLTAGE & CURRENT LIMIT
 1 st STEP.....14.20V - 14-50V
 2 nd STEP.....13.40V - 13-60V
- CHARGER CURRENT : LIMITS CURRENT TO 100% OF FULL LOAD
 : CURRENT DOWN TO SHORT CIRCUIT CONDITION
- PROTECTION : AC.FUSE / DC.FUSE / LOW VOLTAGE CUT OFF TO
 PREVENT BATTERY OVER DISCHARGE
- PANEL METERS : DC.BATTERY VOLTAGE/DC.CHARGE CURRENT
- CONSTRUCTION : ELECTRO GALVANISED STEEL CASE EPOXY POWER COATED
- COMPLIANCE : IEC. 592-2-22
- WEIGHT : 77 KG
- OPTION : AUTOMATIC TEST MOUNTHLY EXERCISE
 : REMOTE TEST WIRELESS
 : TIME DELAY 1 UP TO 10 MINUTES
 : EXHAUST-FAN

MODEL	BATTERY SEALED LEAD ACID	LAMP HEAD	LAMP WATT	DURATION	WEIGHT
CTX12-120C	12V - 120Ah	SQUARE	500	2 HR.	77 KG.