





**MICRO POWER**  
**SELF-CONTAINED EMERGENCY LIGHT**  
 SERIES : MP12-12



**BATTERY**  
**ISO 9002**



## SPECIFICATIONS

INPUT VOLTAGE	:	220 V AC/50Hz +/-10%
TYPE OF BATTERY	:	SEALED LEAD ACID
LAMP USED	:	SEALED DICHROIC TUNGSTEN HALOGEN
MODE OF OPERATION	:	NON MAINTAINED
OPERATING TEMPERATURE	:	Ta 40 C
CHARGER	:	CONSTANT VOLTAGE & CURRENT LIMIT
CHARGER CURRENT	:	LIMITS CURRENT TO 100% OF FULL LOAD CURRENT DOWN TO SHORT CIRCUIT CONDITION
PROTECTION	:	AC.FUSE / DC.FUSE / LOW VOLTAGE CUT OFF TO PREVENT BATTERY OVER DISCHARGE
CONSTRUCTION	:	ELECTRO GALVANISED STEEL CASE EPOXY POWER COATED
COMPLIANCE	:	IEC. 598-2-22

MODEL	BATTERY SEALED LEAD ACID	LAMP HEAD	LAMP WATT	DURATION	WEIGHT
MP12-12CS 20-2	12V - 12Ah	SQUARE	2 x 20 W.	2 HR.30MIN	7 KG.
MP12-12CS 35-2	12V - 12Ah	SQUARE	2 x 35 W.	1 HR.30MIN	7 KG.
MP12-12CS 50-2	12V - 12Ah	SQUARE	2 x 50 W.	1 HR	7 KG.